

一般配管用ステンレス鋼管 (SUS-TPD) (JIS G 3448 : 2012)							銅及び銅合金の棒 (C3601・C3602・C3603・C3604・C3605) (JIS H 3250 : 2010)		
区分	呼び径 Su	外径 mm	外径の許容差		厚さ mm	厚さの 許容差	単位質量 (kg/m)		
			外径	周長			SUS304TPD	SUS315J1TPD SUS315J2TPD SUS316TPD	
直管 及び コイル 巻管	8	9.52	0	-	0.7	±0.12	0.154	0.155	
	10	12.70	-0.37		0.8		0.237	0.239	
	13	15.88			0.8		0.301	0.303	
	20	22.22			1.0		0.529	0.532	
直管	25	28.58			1.0		0.687	0.691	
	30	34.0	±0.34	±0.20	1.2		0.980	0.986	
	40	42.7	±0.43		1.2		1.24	1.25	
	50	48.6	±0.49	±0.25	1.2		1.42	1.43	
	60	60.5	±0.60		1.5	±0.15	2.20	2.21	
	75	76.3	±1%	±0.5%	1.5		2.79	2.81	
	80	89.1			2.0	±0.30	4.34	4.37	
	100	114.3			2.0		5.59	5.63	
	125	139.8			2.0		6.87	6.91	
	150	165.2			3.0	±0.40	12.1	12.2	
	200	216.3			3.0		15.9	16.0	
	250	267.4			3.0		19.8	19.9	
	300	318.5			3.0		23.6	23.8	

銅及び銅合金の継目無管 (1/2) (JIS H 3300 : 2009)